

# T1042

**STEINER**   
Nothing Escapes You

10x power and bright image perfect for sniper/spotters, border surveillance, patrol car optics, and tactical ops day and night.



**APPLICATIONS:**

Standard issue Binocular for Law Enforcement



# 10X42 T1042

**Dimensions (approx.)\***  
167.6 x 124.5 x 63.5 mm  
(6.6 x 4.9 x 2.5 in.)

- **HIGH DEFINITION OPTICS** are specially coated for the highest light transmission, sharp edge-to-edge views and contrast, even in low light.
- **ROOF PRISM DESIGN** is extremely light weight, compact and streamlined, easy to pack, carry, hold and use.
- **TWO-WAY-VALVE-SYSTEM** seals pressurized dry nitrogen into the optic, for fogproof clarity in any condition from arctic cold to desert heat.
- **FAST-CLOSE-FOCUS™** central focusing wheel requires minimal rotation for quick, absolute sharpness from close up to infinity.
- **MILITARY GRADE RUBBER ARMORING** protects chassis and lenses, reduces noise and provides a sure grip in all conditions.
- **CLICLOC® SYSTEM** attaches and releases neck strap or harness instantly with push button ease and designed so binoculars hang straight and action-ready.

ITEM NUMBER 2005




# 10X42r T1042r

**Dimensions (approx.)\***  
167.6 x 124.5 x 63.5 mm  
(6.6 x 4.9 x 2.5 in.)

**Special Features**  
SUMR Milliradian Ranging Reticle

ITEM NUMBER 2006



**SUMR MILLIRADIAN RANGING RETICLE**

Lines and numbers are very thin for extremely accurate measurements.

Magnification	Focus System	Optics Systems	Close Focus	Objective Lens	Exit Pupil	Luminosity	Twilight Factor	Field of View @ 1,000 m	Field of View Angular	Dioptic Range	Interpupillary Distance
10x	Fast-Close-Focus™	High Definition	1.8 m (6 ft.)	42 mm	4.2 mm	17.6	20.5	≥ 105 m	6°	± 4 dpt	56 - 74 mm
Weight	Waterproof	Temperature Range	Eye Relief	Resolving Power	Rubbing Armoring	Eyecups	Neck Strap	Neck Strap Attachment	Objective Cover	Rain Protection Cap	Carry Case
742 g (26 oz.)	Submersion to 1 m (3 ft.)	-20°C to +70°C (-4°F to +158°F)	16 mm	≤ 6"	NBR Long Life	Ergonomic	Neoprene	ClicLoc®	Yes	Yes	Gear Bag

Specifications subject to change without notice.

\*Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.