

T824

STEINER

Nothing Escapes You

Just 350 gr. and incredibly compact, with 8x magnification and wide field of view. Perfect for the gear bag.



APPLICATIONS:

Standard issue Binocular for Military & Law Enforcement



8X24 T824

Dimensions (approx.)*
121.9 x 106.7 x 48.3 mm
(4.8 x 4.2 x 1.9 in.)

ITEM NUMBER 2003

- **HIGH DEFINITION OPTICS** are specially coated for the highest light transmission, sharp edge-to-edge views and contrast, even in low light.
- **ROOF PRISM DESIGN** is extremely light weight, compact and streamlined, easy to pack, carry, hold and use.
- **TWO-WAY-VALVE-SYSTEM** seals pressurized dry nitrogen into the optic, for fogproof clarity in any condition from arctic cold to desert heat.
- **FAST-CLOSE-FOCUS™** central focusing wheel requires minimal rotation for quick, absolute sharpness from close up to infinity.
- **MILITARY GRADE RUBBER ARMORING** protects chassis and lenses, reduces noise and provides a sure grip in all conditions.
- **CLICLOC® SYSTEM** attaches and releases neck strap or harness instantly with push button ease and designed so binoculars hang straight and action-ready.

| Magnification | Focus System | Optics Systems | Close Focus | Objective Lens | Exit Pupil | Luminosity | Twilight Factor | Field of View @ 1,000 m | Field of View Angular | Dioptric Range | Interpupillary Distance |
|----------------|---------------------------|---------------------------------|---------------|-----------------|------------------|------------|-----------------|-------------------------|-----------------------|---------------------|-------------------------|
| 8x | Fast-Close-Focus™ | High Definition | 1.8 m (6 ft.) | 24 mm | 3 mm | 6.8 | 16.1 | ≥ 114 m | 6° | ± 4 dpt | 56 - 74 mm |
| Weight | Waterproof | Temperature Range | Eye Relief | Resolving Power | Rubbing Armoring | Eyecups | Neck Strap | Neck Strap Attachment | Objective Cover | Rain Protection Cap | Carry Case |
| 350 g (12 oz.) | Submersion to 1 m (3 ft.) | -20°C to +70°C (-4°F to +158°F) | 16 mm | ≤ 6" | NBR Long Life | Ergonomic | Neoprene | ClicLoc® | Yes | Yes | Gear Bag |

Specifications subject to change without notice.

*Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.